



BELL HOVER REFILL PUMP

MEDIUM BELL 28VDC HIGH OUTPUT HOVER REFILL PUMP



This high performance, PMA-Approved hover refill pump addresses the needs of the helicopter fire fighting community for reliable and fast filling of helicopter mounted fire tanks.

Features and Components:

- High-output Axial Flow Design
- Impeller and stator for reduced friction losses
- Heavy-Duty Bearing Housing
- Electronically controlled brushless motor
- Soft-start and stall protection
- Infinitely adjustable current limit
- In-pump Data-logger
- Durable Stainless Steel Suction Screen
- Approved for "Transport" category operations without removal of the pump from the aircraft
- Optional Outlet Sizes (4" or 6")

Model 35525 Specifications (Simplex 304 tanks):

Maximum Flow Rate (6" Hose).....	900 GPM
Maximum Flow Rate (4" Hose).....	600 GPM
Pump Weight.....	99LBS
Current Draw.....	100 - 150 AMPS

Model 35540 Specifications (Isolair 4600 eliminator II tanks):

Maximum Flow Rate (6" Hose).....	900 GPM Pump
Weight.....	99LBS
Current Draw.....	100 - 150 AMPS

Both pumps are PMA-approved for replacement on the following popular aircraft: Bell 205, 212/412 and the UH-1H

